



Product Code	ALD-CHR-227
Description	In-wall Body of Manual Shower mixer
Flow Rate	35.00 LPM @ 3 bar
Recommended Water Pressure	0.5 Bar - 5 Bar
Brass Specification in Percentage	Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)
Cartridge Specification	NSF-61 Approved Cartridge with Temperature Limiter Cartridge with Brass Spindle Life Cycle EN 817: 70,000 cycles (Standard) - 2.1 LAC Cycles as per EN 817* - 10.5 LAC Cycles (ON/OFF)*
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Available Colour Finishing	CHROME (CHR)
* As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	