



Product Code	CNF-CHR-69011B
Description	Single Lever Basin Mixer without Popup Waste, with 375mm Long Braided Hoses
Connection Size	"Braided hoses, 1/2\" FIP (WRAS Approved) Withstand pressure of 10 Bar"
Flow Rate	7.63 LPM @ 3 bar
Flow regulator	By using flow regulators (Product should be ordered with suffix as G-2.5, GA-6.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	1.0 Bar - 5 Bar
Brass Specification in Percentage	<p>"Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)"</p>
Cartridge Specification	<p>"NSF-61 Approved Cartridge Cartridge with Metal Spindle Life Cycle EN 817: 70,000 cycles (Standard) - 2.1 LAC Cycles as per EN 817* - 10.5 LAC Cycles (ON/OFF)*"</p>
Water Tightness	16 bar (Pass)
Pressure Resistance	25 bar (Pass)
Finish	"Plating: Nickel-13.0 micron Chromium-0.40 micron Salt Spray (700 hrs + Validated) Adhesion (Pass)"
Aerator Size	M24X1
Available Colour Finishing	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Gold Dust (GDS), Full Gold (GLD), Graphite (GRF), Stainless Steel Finish (SSF) & White Matt (WHM)
* As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	