





OHS-CHR-1679
Maze Prime Square Shape Single Function Shower 450 X 450mm AISI 304 stainless steel with RGB LED light remote control & installation kit for false ceiling • Chromo therapy (RGB): LED x 0.23W with 12V Power Supply (SMPS) Including Controller, connecting to AC 100-240V, 50-60Hz
47.00 LPM @ 3 bar
By using flow regulators + Brass Housing (Product should be ordered with suffix as GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
1.0 Bar - 3.0 Bar
Ceiling Mounting
Single Function
STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm2) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102
Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
276017
Salt Spray (350 hrs + Validated) Adhesion (Pass)
Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Gold Dust (GDS), Full Gold (GLD), Graphite (GRF), Stainless Steel Finish (SSF) & White Matt (WHM)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.

REMOTE CONTROL



LED POWER SUPPLY

• CHROMO THERAPY (RGB) •

LED x 0.23W with 12V Power Supply (SMPS) including Controller, connecting to AC 100-240V, 50-60Hz

• COLOR VARIATION •





LED On / Off
Switch Sensor by Remote Control