artize.com



		 _		-					-	_				
	•	:	0		0	0	0	1		0		0		0
	8									0				
		1.	1	0	0	1	1	8	1.0	1	-		f.	
6	I		:		8	•		8	. 0	•	0		I.	
5			:	6		•		8	10	•	0.		II.	
8	I			-				8	-					
8	1		•		0	• •	• •	0					a.	
8							•••			- 1-	-		U	
8														
1		•				Ar	tize				*			

Product Code	OSA-ACY-70039
Description	Rainjoy Lumos shower 600X472mm RGB LED front panel with AISI 304 stainless steel base plate included remote control & installation kit for false ceiling - Chromo therapy (RGB): LED 36.0W with 12V 5A Power Supply (SMPS) Including Controller, connecting to AC 100-240V, 50-60Hz - 2-functions - Rain - 2 X Water Fall
Flow Rate	Rain - 41.00 LPM @ 3 bar Water Fall - 43.10 LPM @ 3 bar
Recommended Water Pressure	2.0 - 4.0 Bar Min.
Min & Max Water Temperature	5°C ~ 75°C
Mount Type	Ceiling Mounting
Spray Modes	Rain & Waterfall Functions
Material Composition Specification in Percentage	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304)
Fercentage	Acrylic: Acrylic 6T = 6mm thick Acrylic sheet.
REMOTE CONTROL	RGB Remote Control 0 or
IP Rating	1- LED Panel (IP4) 2- SMPS Box (IP7) which includes RGB controller inside
LED Specification	RGB LED Voltage : 12Vdc (minimum electricity goes through LED panel for the user safety) RGB LED Watt : 36.0W
POWER SUPPLY	Power Supply (SMPS) Including Controller INPUT : AC 100-240V, 50-60Hz OUTPUT : 12V - 5A
LED POWER SUPPLY	COLOR VARIATION Mono Color (RGB) Chromo Theraphy LED On / Off Switch Sensor by Remote Control
due to requirements in a	y effort has been made to ensure factual accuracy, the information presented subject to changes different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar ke the necessary amendments at any time without prior notice.